



With built-in PTC fuse. Overload and short-circuit proof.

- 60 VA
- Wall mounting
- Output voltage 24 V AC
- Built-in fuse

Single-phase compact protection transformer for industrial use. The transformer has a low sound level, is protected from humidity, dust and vibrations.

It is cast in self-extinguishing polyurethane with plastic casing.

Class II, double-insulated, short-circuit proof and with a fuse to prevent against overloads.

The casing has mounting-holes and easy accessed wiring terminals under lid. Cable fittings and cable strain reliefs are included.

Range of uses

For supplying HVAC equipment, alarm set-ups, heating foil or -cable, halogen lights and other low-voltage installations (supplying SELV and PELV devices).

TECHNICAL DATA

Power supply:	230 Vac
Output voltage:	24 Vac unstabilized
Power cons.:	15 VA
Frequency:	47...63 Hz
Isolation voltage:	4 kV AC RMS
Temperature rating:	B (130°C)
Max. ambient temperatur:	40°
CE	EMC emissions & immunity standards: This product conforms with the requirements of European EMC standards EN61558-2-6 and carries the CE mark.
Mounting:	panel mounting with screw
Protection:	IP44
Size:	73 x 124 x 67 mm

WIRING AND DIMENSIONS (mm)

